

SAFETY RELIEF VALVE

SR 08 SERIES



INTRODUCTION

The SR-08 are screwed safety relief valves, specially designed and manufactured to **API 520/527**. These valves have been optimized in close cooperation with plant engineers and service specialists, simplifying design with fewer components for less down time, fewer spare parts and lower maintenance costs.

SR-08 has been engineered and designed to provide high quality performance standards for over pressure protection for air, gas, steam and vapour as well as liquid phase applications. This valve provides highly effective solution for various applications as in Pharmaceuticals, Refineries, Chemical Industry, Fertilizer Plant, Petrochemical Industry, Oil & Gas Industry, Storage Tank Systems etc.

FEATURES

- End connection screwed (BSP or NPT) or Flanged
- Adjusting ring
- Inlet connection screwed male or female
- Screwed full nozzle
- Flanges according to ANSI B16.5
- ISO PN Flanges (on request)
- Suitable for thermal relief application
- Nozzle and disc Stellite
- Metal to Metal or Soft seat

SPECIFICATIONS

- **Valve Size** : ½" (DN15) - 1.5" (DN40)
 - **Inlet Rating** : 150# - 2500#
 - **End connection** : Flanged & Screwed
 - **Maximum set pressure** : 420 barg
- Body Materials**
- Carbon Steel
 - Stainless Steel
 - Cr. Mo Steel
 - Low temperature Steel
 - Nickel Copper Alloy
 - Alloy 20

ORDERING INFORMATION

For proper and timely processing of your Enquiry / RFQ or ORDER, the following information should be given:-

- Quantity
- Service Fluid
- Inlet and Outlet Size
- Set Pressure
- Temperature
- Service
- Required Flow Capacity

Please send all your communications to srv@securamax.in